



Technical Specifications PodiumCafé

This is only a summary of our technical facilities, and is subject to change.

We run a 'Fixed Rig' policy. Please call or mail for any further technical background, or general information.

Stage dimensions PodiumCafé:

Depth: 3.00M

Width: 5.00M

Clearance: 3.00M

Height: 0.60M

Sound

Max legal sound limit: 103 dBa over 15 min

Mixing console:

Digital - Midas PRO2c (with DL251, 48 channel stagebox (Firmware G3.4.6))

P.A.:

- 2 -L-Acoustics 115Xt HIQ 15"
- 1 -L-Acoustics LA-8 4 channel amplifier
- 2 - 18" subwoofer
- 2 - Labgruppen 2 channel amplifier Lab 1000

Stage

Monitoring:

- 4 -L-Acoustics 115Xt HIQ 15" floormonitor
- 2 -L-Acoustics LA-8 4 channel amplifier

Drum fill:

- 1 -JBL VRX915M drum fill top 15"+ 1"
- 1 -JBL VRX915S drum fill sub 15"
- 1 -Labgruppen Q2400 (sub)
- 1 -DBX driverack 260



Microphones:

Sufficient various mics

Stands:

Sufficient various stands

Auxiliary Equipment:

- 4 - BSS AR133 DI Box (active)
- 1 - 24 send 4 return stagebox and Multicore to F.O.H. (installed stage Left)

Cable:

Sufficient XLR cable

Lighting

Lighting control:

- 1 - Avolites Quartz v13

Moving light:

- 6 - Martin Rush MH2

Lanterns:

- 13 -Parcan - LED
- 6 -Parcans – Conventional (front)
- 4 -Parcans – Conventional (side)

Visuals

Projection:

- 1 * Optoma W501 (5,000 Lumens)
- 1 * Projection screen (4:3) 300*225 (fixed position stage back)



Electricity

Power:

4 * 16A 220V Ceeform outlet Stage. (Situating Stage Left(1), Back(1) and Right(2))

1 * 16A 220V Ceeform outlet FOH. (Situating FOH connection Cabinet)

Electrical safety:

All incoming electrical equipment should be safe, well maintained and have been portable appliance tested. Although documentation will not strictly be required, evidence of testing should be available. In-house staff will not allow potentially unsafe equipment to be used or connected to the electrical systems.

The Boerderij will assume no responsibility, if the incoming company cannot comply with these requests.